

SculptaCast™

Modeling & Sculpture Waxes


Extrusion Wax Product Data Sheet.

PZ-EX 3011KR Red – Soft.

Precisioned SculptaCast™ Extrusions are formulated to be soft and workable allowing the user to design and construct a bespoke runner system. Available in a range of shapes and sizes, cored and non-cored. The product is manufactured from high grade petroleum and natural raw materials providing consistent results and is naturally clean burning with very low ash residue.

Key benefits

- Easily manipulated, our softest formula
- Superior surface finish
- Ideal for use in temperature controlled or cool environments.



Testing Procedure/Method	Typical Properties
Softening Point, Ring and Ball @4°F/min (IPCS 004)	143°F
Congeaing Point (IPCS 003)	141°F
Flow Test >50% (IPCS 007)	40°C
Needle Penetration 100 g @77°F (IPCS 006)	37.0 dmm
Apparent Viscosity, Brookfield Thermosel @200°F (IPCS 009)	22.0 cps
Ash Content (IPCS 002)	0.005%
Color (IPCS 020)	Red

All manufactured product undergoes stringent Quality Control testing to ensure the highest level of quality and consistency.

Precisioned Ltd has determined test method and provided analysis as noted herein. The levels referenced herein are only for general guidance and do not constitute a firm specification. As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of this product. Information contained herein is believed to be true and accurate but all statements or suggestions are made without warranty, expressed or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. Compliance with all applicable federal, state, and local regulations remains the responsibility of the user. All potential liability related to the sale and use of this product is limited to the cost of the particular goods sold in their respective transactions.

MORSA
D E N T A L